

## • Specification

Input		
Phase / Wire	1 $\phi$ / 2wire	3 $\phi$ / 4wire
Voltage	110/220/380v	208/220/440/600v
Frequency	50/60Hz	
Output		
Voltage Tolerance	Less than $\pm 2\%$	
Frequency Stability	Less than $\pm 0.2\%$	
Total Harmonic Distortion	Less than 3% (at 100% linear load)	
Overload Capacity	120% – 1min	
cooling System	Ventilation by fan with temp. sensor	
Energy Storage Device	Ultracapacitor	
Power Back-up Durations	1sec (at 70% load) It can be changed by customer request	

## • Models

	Model	Rating	Dimension
Single-Phase Series	ECC1-001CM	1KVA	300X580X800
	ECC1-003CM	3KVA	300X580X800
	ECC1-005CM	5KVA	300X580X950
	ECC1-007CM	7KvA	400X750X800
	ECC1-010CM	10KVA	400X750X1100
Three-Phase Series	ECC3-007CM	7KVA	480X750X1000
	ECC3-010CM	10KVA	480X750X1100
	ECC3-015CM	15KVA	480X750X1400
	ECC3-300CL	300KVA	2600X1000X2000
	ECC3-500CL	500KVA	4000X1000X2000